

Product information



GMS Lens Seal 8x3.8 mm, 2x120° Convex, Brass

Art.Nr.: GMS-LINSE- / manufacturer: [HEL Performance \(UK\)](#)



2,40 EUR / pcs.

incl. 19% VAT plus 7,60 EUR DHL-Shipping

 Ready for dispatch within 1-2 working days. Delivery time approx. 3-5 working days!

Lens seal, brass, 8x3.8 mm, 3 mm bore, 2x120° convex sealing cone.

The lens gasket is suitable for connecting certain fittings to one another. It is often used for connecting to metal lines.

Please note that the connector blocks in HEL Performance's ABS line kits are designed such that this lens gasket is NOT required. With HEL Performance, the sealing cone is already integrated into the connector block. By its very nature, a lens gasket must seal on both sides. However, if the sealing cone is already present in the connector—as is the case with HEL Performance—only one surface needs to be sealed. In our view, this provides greater operational reliability. It is also likely easier to handle during installation.

In some applications, however, a lens gasket is required. That is why we offer it as an accessory.

Package contents: 1 x lens gasket

Material: Brass

Product information



You can find steel-braided
online shop at:

motorrad.helperformance.de (please click on the link)

HEL-Performance® brake line kit, including hollow screws** and accessories**

- No line expansion at high temperatures
- Eliminates the spongy feeling in the brake lever
- Direct and precise braking response
- Teflon inner liner with stainless steel sheath
- Exclusively stainless steel fittings
- Lower maintenance costs for the braking system
- Technology proven in motorsports

* For information on availability and delivery with ABE or component certification, please refer to the latest version of our ABE, which you can download here as a PDF file:

www.helperformance.com/certification

The ABE is continuously updated. If your vehicle is not listed, or not yet listed, please contact us directly.

(** is included, if required)