

Product information



HEL copper sealing rings, 10mm, 2mm thick

Art.Nr.: HEL-CCW-10-2 / manufacturer: [HEL Performance \(UK\)](#)



0,29 EUR / pcs.

incl. 19% VAT plus 7,60 EUR DHL-Shipping

 Ready for dispatch within 1-2 working days. Delivery time approx. 3-5 working days!



HEL-Performance® copper sealing rings for 10mm ring connections/screws

Nominal dimensions: 10x15x2mm

Product information



Sold in packs of 10
(order quantity 10 pieces, 20 pieces e

Tighten brake lines, banjo bolts and connections!

Note Tightening torque for:

- Stainless steel fitting and stainless steel banjo bolts Min. 20 Nm - Max. 33 Nm.
- Stainless steel fitting and aluminum banjo bolt Min. 18 Nm - Max. 21 Nm.
- Aluminum fitting and stainless steel banjo bolt Min. 18 Nm - Max. 21 Nm.
- Aluminum fitting and aluminum banjo bolt Min. 18 Nm - Max. 21 Nm.

The vehicle manufacturer's tightening values must not be exceeded!

Braided steel brake lines and kits from HEL Performance:

HEL-Performance® brake line kit, including banjo bolts** and accessories**

- No expansion of the lines at high temperatures
- eliminates the spongy feeling on the brake lever
- direct and precise braking point
- Teflon inner core with stainless steel sheathing
- only stainless steel connections
- Lower maintenance costs for the brake system
- Motorsport proven technology

* For availability and delivery with ABE or parts certificate, please refer to the latest version of our ABE, which you can download here as a PDF file:

www.help erformance.com/certification

The ABE is updated on an ongoing basis. If your vehicle is not or not yet included, please contact us directly.

(** is included, if required)